



歐規PVC汽車用線 FLY

ISO Automotive Wire FLY

Product Description :

- Conductor : Soft-annealed conductor
- Insulation : Soft-PVC
- Temperature Rated: -40°C ~ + 105°C
- Standard : ISO 6722-1, Class B

產品說明 :

- 導體：軟銅絞線
- 絕緣：柔軟 PVC
- 耐溫：-40°C ~ + 105°C
- 符合歐洲規範：ISO 6722-1, Class B

導體 Conductor		絕緣 Insulation	完成外徑 Overall Diameter		最大導體阻抗 Max Conductor Resistance at 20°C	
截面積 Cross-Section	構成 Stranded		絞合外徑 Diameter	平均厚度 Thickness		標準線徑 Standard
mm ²	No. /mm	mm	mm	mm	mm	mΩ/m
0.5	16/0.21	1.00	0.60	2.30	-0.30	37.10
0.75	24/0.21	1.20	0.60	2.50	-0.30	24.70
1	32/0.21	1.35	0.60	2.70	-0.30	18.50
1.25	16/0.33	1.70	0.60	2.95	-0.55	14.90
1.5	30/0.26	1.70	0.60	3.00	-0.30	12.70
2	28/0.31	2.00	0.60	3.30	-0.30	9.42
2.5	50/0.26	2.20	0.70	3.60	-0.30	7.60
3	60/0.26	2.40	0.70	4.10	-0.30	6.15
4	56/0.31	2.75	0.80	4.40	-0.40	4.71
5	65/0.33	3.10	0.80	4.90	-0.40	3.94
6	84/0.31	3.30	0.80	5.00	-0.40	3.14
8	50/0.46	4.30	0.80	5.90	-0.90	2.38
10	80/0.41	4.50	1.00	6.50	-0.50	1.82
12	96/0.41	5.40	1.00	7.40	-0.80	1.52
16	126/0.41	6.30	1.00	8.30	-0.60	1.16
20	152/0.41	6.90	1.10	9.10	-1.00	0.955
25	196/0.41	7.80	1.30	10.40	-0.70	0.743
30	224/0.41	8.30	1.30	10.90	-1.20	0.647
35	276/0.41	9.00	1.30	11.60	-0.60	0.527
40	308/0.41	9.60	1.40	12.40	-1.20	0.473
50	396/0.41	10.50	1.50	13.50	-2.00	0.368
60	296/0.51	11.60	1.50	14.60	-1.20	0.315
70	360/0.51	12.50	1.50	15.50	-2.00	0.259
95	475/0.51	14.80	1.60	18.00	-2.00	0.196
120	608/0.51	16.50	1.60	19.70	-2.00	0.153