



歐規柔軟耐寒汽車用線 FLYK

ISO Automotive Wire FLYK with flexibility

Product Description :

- Conductor : Soft-annealed conductor
- Insulation : Soft-PVC, Cold resistant
- Temperature Rated: -50°C ~ + 105°C
- Standard : ISO 6722-1, Class B

產品說明 :

- 導體：軟銅絞線
- 絕緣：柔軟 PVC 可耐寒 -50°C
- 耐溫：-50°C ~ + 105°C
- 符合歐洲規範：ISO 6722-1, Class B

| 導體 Conductor | | 絕緣 Insulation | 完成外徑 Overall Diameter | | 最大導體阻抗 Max Conductor Resistance at 20°C | |
|----------------------|----------------|------------------|--------------------------|------------------|--|-------|
| 截面積 Cross-Section | 構成 Stranded | 絞合外徑 Diameter | 平均厚度 Thickness | 標準線徑 Standard | 公差值 Tolerance | |
| mm ² | No. /mm | mm | mm | mm | mm | mΩ/m |
| 0.5 | 28/0.16 | 1.00 | 0.60 | 2.30 | -0.30 | 37.10 |
| 0.75 | 42/0.16 | 1.30 | 0.60 | 2.50 | -0.30 | 25.10 |
| 1 | 57/0.16 | 1.50 | 0.60 | 2.70 | -0.30 | 18.80 |
| 1.5 | 84/0.16 | 1.80 | 0.60 | 3.00 | -0.30 | 12.70 |
| 2.5 | 140/0.16 | 2.30 | 0.70 | 3.90 | -0.40 | 7.54 |
| 4 | 1015/0.08 | 3.30 | 0.80 | 4.90 | -0.40 | 4.71 |
| 6 | 1548/0.08 | 4.20 | 0.80 | 5.90 | -0.40 | 3.14 |
| 10 | 2510/0.08 | 5.20 | 1.00 | 7.30 | -0.60 | 1.85 |
| 16 | 4033/0.08 | 6.70 | 1.00 | 8.80 | -0.60 | 1.16 |
| 25 | 3169/0.11 | 8.00 | 1.20 | 10.50 | -0.60 | 0.743 |