



美規 XLPE汽車用線 TXL

Thin-wall with XLPE TXL

Product Description :

- Conductor : Soft-annealed conductor
- Insulation : Cross-linked PE
- Temperature Rated: -40°C ~ + 125°C
- Standard : SAE J1128

產品說明 :

- 導體：軟銅絞線
- 絕緣：照射 PE 材質
- 耐溫：-40°C ~ + 125°C
- 符合美國規範：SAE J1128

構造 Construction



導體 Conductor		絕緣厚度 Insulation			完成外徑 Overall Diameter	大約重量 Approx. Weight
截面積 Cross-Section	構成 Stranded	絞合外徑 Diameter	平均厚度 Thickness	最小厚度 Thickness	標準線徑 Standard	
AWG	No. /mm	mm	STD (mm)	MIN (mm)	mm	kg/km
24	7/0.254	0.78	0.28	0.40	1.70	5.4
22	7/0.254	0.78	0.28	0.40	1.70	5.4
20	7/0.32	0.98	0.28	0.40	1.90	7.7
18	19/0.24	1.17	0.28	0.40	2.20	10.7
16	19/0.29	1.46	0.28	0.40	2.40	14.6
14	19/0.361	1.82	0.28	0.40	2.70	22.0
12	19/0.45	2.27	0.32	0.46	3.30	34.0
10	19/0.57	2.87	0.35	0.50	4.00	53.0