




UL10533


Product Description

 **Rated voltage**
600V

 **Rated temperature**
60°C / 80°C / 90°C

 **Fire Performances**
Horizontal flame


 **AWG**
36AWG-14AWG

 **Conductor**
Solid/ Stranded

 **Insulation**
FRPE

 **Bend Radius**
10X

Marking Example:
E209277 cUL AWM STYLE 10533 60°C 600V FT2 □□AWG
3A AWM IA 60°C 600V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
14	41/0.254	1.88	0.24	2.35±0.1
16	26/0.254	1.50	0.24	1.97±0.1
18	34/0.18	1.21	0.24	1.69±0.1
20	21/0.18	0.95	0.24	1.50±0.1
22	17/0.16	0.76	0.24	1.24±0.1
24	11/0.16	0.62	0.24	1.09±0.1
26	7/0.16	0.49	0.24	0.96±0.1
28	7/0.127	0.39	0.24	0.90±0.1
30	7/0.10	0.31	0.24	0.78±0.1
32	7/0.08	0.24	0.24	0.72±0.1
34	7/0.06	0.18	0.24	0.66±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners