




UL 1095


Product Description

 **Rated voltage**
300V


 **Rated temperature**
80°C

 **Fire Performances**
Horizontal flame


 **AWG**
30AWG-16AWG

 **Conductor**
Solid / Stranded

 **Insulation**
PVC

 **Bend Radius**
10X

Marking Example:
E209277 cUL AWM STYLE 1095 80°C 300V FT2 □□AWG
3A AWM IA 80°C 300V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
16	26/0.254	1.50	0.36	2.23±0.1
18	34/0.18	1.21	0.36	1.94±0.1
20	21/0.18	0.95	0.36	1.68±0.1
22	17/0.16	0.76	0.36	1.49±0.1
24	11/0.16	0.62	0.36	1.34±0.1
26	7/0.16	0.49	0.36	1.22±0.1
28	7/0.127	0.39	0.36	1.12±0.1
30	7/0.10	0.31	0.36	1.04±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners