



600V FEP Wire

UL 1330

Product Description



Rated voltage

600V



Rated temperature

200°C



Fire Performances

Horizontal flame



AWG

30AWG-4/0AWG



Conductor

Solid / Stranded(Silver Plated)



Insulation

PVC



Covering

Optional (FEP)



Bend Radius

5X

Marking Example:

E209277 cUL AWM STYLE 1330 200°C 600V FT2 □□AWG
3A AWM IA 200°C 600V □□AWG FT2 3A LF

FEP Insulation (鐵氟龍絕緣)

Conductor(導體)



Conductor		Insulation		OVERALL DIAMETER
AWG	Stranded (No./mm)	Insulation Thickness (mm)	Covering (mm)	
線規	線規/線徑	絕緣厚度(mm)	外被厚度(mm)	完成外徑(mm)
4/0	2146/0.254	1.20	0.31	16.62±0.1
3/0	1615/0.254	1.20	0.31	14.82±0.1
2/0	1330/0.254	1.20	0.31	13.73±0.1
1/0	1026/0.254	1.20	0.31	12.43±0.1
2	665/0.254	0.82	0.31	9.84±0.1
4	420/0.254	0.82	0.31	8.28±0.1
6	259/0.254	0.82	0.31	7.20±0.1
8	161/0.254	0.82	0.31	5.98±0.1
10	105/0.254	0.57	0.31	4.77±0.1
12	65/0.254	0.57	0.31	4.13±0.1
14	41/0.254	0.57	0.31	3.64±0.1
16	26/0.254	0.57	0.31	3.26±0.1
18	34/0.18	0.57	0.31	2.20±0.1
20	21/0.18	0.57	0.31	2.05±0.1
22	17/0.16	0.57	0.31	2.53±0.1
24	11/0.16	0.57	0.31	2.38±0.1
26	7/0.16	0.57	0.31	2.25±0.1
28	7/0.127	0.57	0.31	2.15±0.1
30	7/0.10	0.57	0.31	2.07±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners