



UL 1777

Product Description

Rated voltage
300V

Rated temperature
80°C

Fire Performances
FT2 flame

AWG
30AWG-16AWG

Conductor
Solid / Stranded


Insulation
SRPVC

Shield
Optional

Jacket
PVC

Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 1777 80°C 300V FT2 □□AWG
3A AWM IA 80°C 300V □□AWG FT2 3A LF



Conductor		Insulation		OVERALL DIAMETER
AWG 線規	Stranded (No./mm) 線規/線徑	Insulation Thickness (mm) 絕緣厚度(mm)	Covering (mm) 外被厚度(mm)	
16	26/0.254	0.29	0.82	3.72±0.10
18	34/0.18	0.29	0.82	3.43±0.10
20	21/0.18	0.29	0.82	3.17±0.10
22	17/0.16	0.29	0.82	2.98±0.10
24	11/0.16	0.29	0.82	2.83±0.10
26	7/0.16	0.29	0.82	2.71±0.10
28	7/0.127	0.29	0.82	2.61±0.10
30	7/0.10	0.29	0.82	2.53±0.10

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners