

125V FRPE Cable



三甲電線電纜
3A PLUS
WIRE & CABLE

UL 21269

Product Description



Rated voltage

125V



Rated temperature

80°C



Fire Performances

Cable flame



AWG

30AWG-4/0AWG



Conductor

Solid / Stranded



Insulation

UL Labeled



Assembly

2 or more insulated singles twisted together.



Covering / Jacket

FRPE(Optional)

FRPE




Bend Radius

10X

Marking Example:

E209277 cUL AWM STYLE 21269 80°C 125V VW-1 □□AWG
3A AWM 1A 80°C 125V □□AWG VW-1 3A LF



Conductor			Insulation		
AWG 線規	Stranded (No./mm) 線規/線徑	Cores (N) 芯線(C)	Insulation overall Diameter(mm) 芯線直徑(mm)	Covering&Jacket of Thickness(mm) 外被厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
16	26/0.254	2	2.13	0.76	4.97±0.1
	34/0.18	2	1.84	0.76	4.60±0.1
18	34/0.18	3	1.84	0.76	5.20±0.1
	21/0.18	2	1.58	0.76	4.10±0.1
20	21/0.18	3	1.58	0.76	4.70±0.1
	17/0.16	2	1.40	0.76	3.90±0.1
22	17/0.16	3	1.40	0.76	4.40±0.1
	11/0.16	2	1.25	0.76	3.60±0.1
24	11/0.16	3	1.25	0.76	4.10±0.1
	7/0.16	2	1.13	0.76	3.40±0.1
26	7/0.16	3	1.13	0.76	3.80±0.1
	7/0.127	2	1.03	0.76	3.20±0.1
28	7/0.127	3	1.03	0.76	3.60±0.1
	7/0.10	2	0.94	0.76	3.10±0.1
30	7/0.10	3	0.94	0.76	3.50±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.

Other logos, product and/or Company names may be trademarks of their respective owners