

300V FRPE Cable

UL 21307
Product Description

Rated voltage
300V

Rated temperature
80℃

Fire Performances
Horizontal flame

AWG
Not Specified

Conductor
Solid / Stranded


Insulation
UL Labeled

Assembly
2-more conductors (twisted singles
/ groups /laid parallel to form flat,
oval, or round cables)

Shield / Covering
Optional

Jacket
FRPE

Bend Radius
10X



Conductor			Insulation		
AWG 線規	Stranded (No./mm) 線規/線徑	Cores (N) 芯線(C)	Insulation overall Diameter(mm) 芯線直徑(mm)	Jacket of Thickness(mm) 外被厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
24	7/0.16	3	1.25	0.41	3.20±0.1
	7/0.16	4	1.25	0.41	3.50±0.1
28	7/0.127	6	1.03	0.41	3.40±0.1
	7/0.127	6	1.03	0.76	4.20±0.1
	7/0.127	8	1.03	0.41	3.70±0.1
	7/0.127	8	1.03	0.76	4.60±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners

Marking Example:
E209277 cUL AWM STYLE 21307 80°C 300V FT2 □□AWG
3A AWM 1A 80°C 300V □□AWG FT2 3A LF

