



UL 2569

Product Description



Rated voltage

600V



Rated temperature

105°C



Fire Performances

Horizontal flame



AWG

30AWG-10AWG



Conductor

Solid / Stranded



Insulation

PVC



Assembly

2-12 conductors.Flat ribbon cable.



Bend Radius

10X

Marking Example:

E209277 cUL AWM STYLE 2569 105°C 600V FT2 □□AWG
 3A AWM 1A 105°C 600V □□AWG FT2 3A LF



Conductor				Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Cores (N) 芯數	Insulation of Thickness(mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
10	105/0.254	3.01	2F	0.82	4.7x9.4±0.1
16	26/0.254	1.50	2F	0.82	3.2x6.4±0.1
18	34/0.18	1.21	2F	0.82	2.9x5.8±0.1
20	21/0.18	0.95	2F	0.82	2.6x5.2±0.1
22	17/0.16	0.76	2F	0.82	2.5x5.0±0.1
24	11/0.16	0.62	2F	0.82	2.3x4.6±0.1
26	7/0.16	0.49	2F	0.82	2.1±4.20.1
28	7/0.127	0.39	2F	0.82	2.0x4.0±0.1
30	7/0.10	0.31	2F	0.82	1.95x3.9±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.

Other logos, product and/or Company names may be trademarks of their respective owners