

300V PVC Cable

UL 2785
Product Description

Rated voltage
300V

Rated temperature
60°C

Fire Performances
Horizontal flame

AWG
UL Labeled

Conductor
Solid / Stranded

Insulation
UL Labeled

Assembly
2-more

Shield / Covering
Optional

Jacket
PVC

Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 2785 80°C 300V FT2 □□AWG
3A AWM IA 80°C 300V □□AWG FT2 3A LF



Conductor			Insulation			
AWG 線規	Stranded (No./mm) 線規/線徑	Cores (N) 芯線(C)	Insulation overall Diameter(mm) 芯線直徑(mm)	Covering&Jacket of Thickness(mm) 外被厚度(mm)		OVERALL DIAMETER 完成外徑(mm)
28	7/0.127	3	1.03	0.15	0.38	3.11±0.10
	7/0.127	4	1.03	0.15	0.38	3.46±0.10
	7/0.127	6	1.03	0.15	0.38	4.00±0.10
	7/0.127	8	1.03	0.15	0.38	4.50±0.10
	7/0.127	10	1.03	0.15	0.38	4.83±0.10
30	7/0.10	3	0.94	0.15	0.38	2.95±0.10
	7/0.10	4	0.94	0.15	0.38	3.24±0.10
	7/0.10	6	0.94	0.15	0.38	3.71±0.10
	7/0.10	8	0.94	0.15	0.38	4.13±0.10
	7/0.10	10	0.94	0.15	0.38	4.50±0.10

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners