



600V SR-Silicone Wire

UL 3074

Product Description

 Rated voltage
600V

 Rated temperature
200°C

 Fire Performances
Horizontal flame

 AWG
32AWG-10AWG


 Conductor
Solid / Stranded(Silver plated)

 Insulation
SR-Silicone

 Covering
Type SF-2

 Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 3074 200°C 600V FT2 □□AWG
3A AWM IA 200°C 600V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
10	105/0.254	3.01	0.44	4.2±0.1
12	65/0.254	2.37	0.44	3.30±0.1
14	41/0.254	1.88	0.44	3.80±0.1
16	26/0.254	1.50	0.44	2.40±0.1
18	34/0.18	1.21	0.44	2.10±0.1
20	21/0.18	0.95	0.44	1.80±0.1
22	17/0.16	0.76	0.44	1.65±0.1
24	11/0.16	0.62	0.44	1.49±0.1
26	7/0.16	0.49	0.44	1.37±0.1
28	7/0.127	0.39	0.44	1.27±0.1
30	7/0.10	0.31	0.44	1.19±0.1
32	7/0.08	0.24	0.44	1.13±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners