



UL 3135  
Product Description



Rated voltage  
600V

Rated temperature  
200°C

Fire Performances  
Horizontal flame

AWG  
26AWG-12AWG

Conductor  
Solid / Stranded(Silver plated)

Insulation  
SR

Bend Radius  
10X

Marking Example:  
E209277 cUL AWM STYLE 3135 200°C 600V FT2 □□AWG  
3A AWM IA 200°C 600V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
12	65/0.254	2.37	0.82	4.01±0.1
14	41/0.254	1.88	0.82	3.52±0.1
16	26/0.254	1.50	0.82	3.14±0.1
18	34/0.18	1.21	0.82	2.86±0.1
20	21/0.18	0.95	0.82	2.60±0.1
22	17/0.16	0.76	0.82	2.41±0.1
24	11/0.16	0.62	0.82	2.26±0.1
26	7/0.16	0.49	0.82	2.13±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.  
Other logos, product and/or Company names may be trademarks of their respective owners