




# UL 3290


## Product Description

 Rated voltage  
**600V**


 Rated temperature  
**125°C**

 Fire Performances  
**Horizontal flame**


 AWG  
**26AWG-9AWG**

 Conductor  
**Solid / Stranded**

 Insulation  
**XLPE**

 Bend Radius  
**10X**

Marking Example:  
E209277 cUL AWM STYLE 3290 125°C 600V FT2 □□AWG  
3A AWM IA 125°C 600V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
10	105/0.254	3.01	1.58	6.17±0.1
12	65/0.254	2.37	1.58	5.53±0.1
14	41/0.254	1.88	1.58	5.05±0.1
16	26/0.254	1.50	1.58	4.66±0.1
18	34/0.18	1.21	1.58	4.38±0.1
20	21/0.18	0.95	1.58	4.12±0.1
22	17/0.16	0.76	1.58	3.93±0.1
24	11/0.16	0.62	1.58	3.78±0.1
26	7/0.16	0.49	1.58	3.66±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.  
Other logos, product and/or Company names may be trademarks of their respective owners