



UL 3610

Product Description

 **Rated voltage**
300V

 **Rated temperature**
105°C

 **Fire Performances**
Horizontal flame

 **AWG**
36AWG-16AWG

 **Conductor**
Solid / Stranded

 **Insulation**
XLPVC

 **Shield**
Optional

 **Covering**
Optional / XLPVC

 **Bend Radius**
10X

Marking Example:
E209277 cUL AWM STYLE 3610 105°C 300V FT2 □□AWG
3A AWM IA 105°C 300V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
16	26/0.254	1.50	0.20	1.90±0.10
18	34/0.18	1.21	0.20	1.62±0.10
20	21/0.18	0.95	0.20	1.36±0.10
22	17/0.16	0.76	0.20	1.17±0.10
24	11/0.16	0.62	0.20	1.02±0.10
26	7/0.16	0.49	0.20	0.88±0.10
28	7/0.127	0.39	0.20	0.80±0.10
30	7/0.10	0.31	0.20	0.71±0.10
32	7/0.08	0.24	0.20	0.65±0.10
34	7/0.06	0.18	0.20	0.59±0.10

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners