



UL11109
Product Description

⚡ Rated voltage
600V

🌡️ Rated temperature
105°C

🔥 Fire Performances
Horizontal flame


🔌 AWG
32AWG-10AWG

📦 ²⁹CU Conductor
Solid/ Stranded

🌀 Insulation
PVC

🕒 Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 11109 105°C 600V FT2 □□AWG
3A AWM IA 105°C 600V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
10	105/0.254	3.01	0.57	4.14±0.1
12	65/0.254	2.37	0.57	3.60±0.1
14	41/0.254	1.88	0.57	3.01±0.1
16	26/0.254	1.50	0.57	2.90±0.1
18	34/0.18	1.21	0.57	2.35±0.1
20	21/0.18	0.95	0.57	2.09±0.1
22	17/0.16	0.76	0.57	1.90±0.1
24	11/0.16	0.62	0.57	1.75±0.1
26	7/0.16	0.49	0.57	1.62±0.1
28	7/0.127	0.39	0.57	1.52±0.1
30	7/0.10	0.31	0.57	1.44±0.1
32	7/0.08	0.24	0.57	1.38±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners