



UL 21279

Product Description



Rated voltage

600V

Rated temperature

80°C

Fire Performances

Horizontal flame

AWG

40AWG min

Conductor

Solid / Stranded

Insulation

UL Labeled

Assembly

2-more condutors(twisted pairs /
groups /laid parallel to form flat,
oval, or round cables)




Shield / Covering

Optional**Optional / FRPE / PVC**

Jacket

FRPE

Bend Radius

10X

Conductor			Insulation			
AWG 線規	Stranded (No./mm) 線規/線徑	Cores (N) 芯線(C)	Insulation overall Diameter(mm) 芯線直徑(mm)	Covering&Jacket of Thickness(mm) 外被厚度(mm)		OVERALL DIAMETER 完成外徑(mm)
18	34/0.18	2	1.84	0.23	0.41	5.40±0.1
	34/0.18	3	1.84	0.23	0.41	7.40±0.1
20	21/0.18	2	1.58	0.23	0.41	4.80±0.1
	21/0.18	3	1.58	0.23	0.41	6.90±0.1
22	17/0.16	2	1.40	0.23	0.41	4.20±0.1
	17/0.16	3	1.40	0.23	0.41	6.30±0.1
24	11/0.16	2	1.25	0.23	0.41	4.00±0.1
	11/0.16	3	1.25	0.23	0.41	5.90±0.1
26	7/0.16	2	1.13	0.23	0.41	3.80±0.1
	7/0.16	3	1.13	0.23	0.41	5.70±0.1
28	7/0.127	2	1.03	0.23	0.41	3.70±0.1
	7/0.127	3	1.03	0.23	0.41	5.50±0.1
30	7/0.10	2	0.94	0.23	0.41	3.40±0.1
	7/0.10	3	0.94	0.23	0.41	5.30±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.

Other logos, product and/or Company names may be trademarks of their respective owners

Marking Example:
 E209277 cUL AWM STYLE 21279 80°C 600V VW-1 □□AWG
 3A AWM 1A 80°C 600V □□AWG VW-1 3A LF
