

Automotive Wires &amp; Cables

3A PLUS  
WIRE & CABLE

# JASO D611

## AVS Series

Thin Wall 2



Rated temperature

**-40°C - 80°C**

Conductor

**Soft-annealed  
stranded copper**

Insulation

**PVC**

導體 conductor			絕緣厚度 Insulation	完成外徑 OD		最大導體阻抗 Max Conductor Resistance at 20°C(Ω/m)
截面積 Cross- Section(mm²)	構成 Stranded(No./mm)	絞合外徑 Diameter (mm)	平均厚度 Thickness(mm)	標準線徑 Standard (mm)	最大線徑 Max.(mm)	
0.3f	15/0.18	0.8	0.5	1.8	1.9	48.9
0.3	7/0.26	0.8	0.5	1.8	1.9	50.2
0.5f	20/0.18	1	0.5	2	2.1	36.7
0.5	7/0.32	1	0.5	2	2.1	32.7
0.75f	30/0.18	1.2	0.5	2.2	2.3	24.4
0.85	16/0.26	1.2	0.5	2.2	2.3	22
1.25f	50/0.18	1.5	0.6	2.5	2.6	14.7
1.25	16/0.32	1.5	0.6	2.5	2.6	14.3
2	26/0.32	1.9	0.6	2.9	3.1	8.81
2f	37/0.26	1.8	0.6	2.9	3.1	9.5
3	41/0.32	2.4	0.7	3.6	3.8	5.59
5	65/0.32	3	0.8	4.4	4.6	2.52

Note. 1 \* f in the specification indicates a stranded conductor.