

Automotive Wires & Cables

3A PLUS
WIRE & CABLEJASO D611 

AVSS Series

Super Extra Thin Wall



Rated temperature

-40°C-80°C

Conductor

**Soft-annealed
stranded copper**

Insulation

PVC

導體 conductor			絕緣厚度 Insulation	完成外徑 OD		最大導體阻抗 Max Conductor Resistance at 20°C(Ω/m)
截面積 Cross- Section(mm²)	構成 Stranded(No./mm)	絞合外徑 Diameter (mm)	平均厚度 Thickness(mm)	標準線徑 Standard (mm)	最大線徑 Max.(mm)	
0.3f	19/0.16	0.8	0.3	1.4	1.5	48.8
0.3	7/0.26	0.8	0.3	1.4	1.5	50.2
0.5f	19/0.19	1	0.3	1.6	1.7	34.6
0.5	7/0.32	1	0.3	1.6	1.7	32.7
0.75f	19/0.23	1.2	0.3	1.8	1.9	23.6
0.85	19/0.24	1.2	0.3	1.8	1.9	22
1.25f	37/0.21	1.5	0.3	2.1	2.2	14.6
1.25	19/0.29	1.5	0.3	2.1	2.2	14.9
2f	37/0.26	1.8	0.4	2.6	2.7	9.5

Note. 1 * f in the specification indicates a stranded conductor.