

Automotive Wires & Cables

JASO D611 

AVSSH

Heat-Resistant 1

Thin Wall 2



Rated temperature

-40°C - 100°C

29
CU

Conductor

Soft-annealed

stranded copper



Insulation

PVC

導體 conductor			絕緣厚度 Insulation	完成外徑 OD		最大導體阻抗Max Conductor Resistance at 20°C(Ω/m)
截面積	構成	絞合外徑	平均厚度	標準線徑	最大線徑	
Cross- Section(mm²)	Stranded (No./mm)	Diameter (mm)	Thickness(mm)	Standard (mm)	Max.(mm)	
0.3f	19/0.16	0.8	0.3	1.4	1.5	48.8
0.5f	19/0.19	1	0.3	1.6	1.7	34.6
0.75f	19/0.23	1.2	0.3	1.8	1.9	23.6
1.25f	37/0.21	1.5	0.3	2.1	2.2	14.6
2f	39/0.26	1.8	0.4	2.6	2.7	9.5

Note. 1 * f in the specification indicates a stranded conductor.

EBX

Heat-Resistant 1

Ground Wire



Rated temperature

-40°C - 100°C

29
CU

Conductor

Soft-annealed

stranded copper



Insulation

XLPVC

導體 conductor			絕緣厚度 Insulation	完成外徑 OD		最大導體阻抗 Max Conductor Resistance at 20°C(Ω/m)
截面積	構成	絞合外徑	平均厚度	標準線徑	最大線徑	
Cross- Section(mm²)	Stranded(No./mm)	Diameter (mm)	Thickness (mm)	Standard (mm)	Max.(mm)	
15	19/9/0.32	5.3	0.6	6.5	6.9	1.37
20	19/13/0.32	6.5	0.6	7.7	8.1	0.946
30	19/19/0.32	7.8	0.6	9	9.4	0.647

Note. 1 * f in the specification indicates a stranded conductor.