



UL 21283

Product Description

 **Rated voltage**
30V

 **Rated temperature**
80°C

 **Fire Performances**
Horizontal flame

 **AWG**
40AWG min

 **Conductor**
Solid / Stranded

 **Insulation**
UL Labeled

 **Assembly**
2-more condutors(twisted pairs / groups /laid parallel to form flat, oval, or round cables)

 **Shield / Covering**
Optional
Optional / FRPE / PVC

 **Jacket**
FRPE

 **Bend Radius**
10X



Conductor			Insulation			
Cores (N) 芯線	AWG 線規	Stranded (No./mm) 線規/線徑	Insulation OD(mm) 芯線直徑(mm)	Covering&Jacket of Thickness(mm) 外被厚度(mm)		OVERALL DIAMETER 完成外徑(mm)
2F	10	105/0.254	3.46	0.15	0.76	7X12±0.1
	18	34/0.18	1.85	0.15	0.76	
3+4 (c)	22	17/0.16	1.40	0.15	0.76	10.00±0.1
	18	34/0.16	1.85	0.15	0.76	
4+6 (c)	22	17/0.16	1.40	0.15	0.76	10.80±0.1
	18	34/0.16	1.85	0.15	0.76	

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners

Marking Example:
E209277 cUL AWM STYLE 21283 80°C 30V FT2 □□AWG
3A AWM 1A 80°C 30V □□AWG FT2 3A LF

