




# USB 4.0 / 3.2 Gen.2x2 Key A 20M Internal-to-External Cable




**Product Description**     *Converts USB 4.0/3.2 Gen.2 signal from motherboard to front panel / Hot-swappable, reversible plug external output*

<b>Product Features</b>	<b>Ultra-Thin</b> 1.25mm	<b>High Speed</b> 10/20 Gbps	<b>Internal to External</b> M/B USB to front panel , hot-swapp, reversble
-------------------------	-----------------------------	---------------------------------	---



Adapter 3.1C Int. Key A 20M



Key A 20F



Key A 20M



Type C 24M ( HOST)



C24M w/Ear



3.1C 24F  
C24M R/A



3.1C24F



U3mB10M



U3 A9M



U3 A9F



U3 A9F with EAR



U3\_Int\_20F

## Specifications

Item	Key A 20M series
USB version	USB 4.0 / 3.2 Gen.2x2
Connector type	Key A 20M/F / C24F w/Ear /C24F R/A and more
Cable lengh	Up to 100cm
Transfer speed	20 Gbps (Type-C) 10 Gbps (Type-A)
Output power	3A / 5V (Intel specification)



## Connector Type Reference

P/N	Description
5R24A02-A	Adapter 3.1C Int. Key A 20M (molded)
5G20A37-1xxxx	Key A 20M to Key A 20F
5G24D51-1xxxx	Type C 24M (Host) to Key A 20F
5G24D52-1xxxx	Type C 24M to Key A 20F (Host)
5G20A11-1xxxx	Key A 20M ×2
5G24A12-1xxxx	Key A 20M to Type C 24F (R/A)
5G20A13-1xxxx	Key A 20M to USB 3.0 Micro-B 10M
5G20A14-1xxxx	Key A 20M to USB 3.0 A9F
5G20A15-1xxxx	Key A 20M to USB 3.0 A9M
5G20A27-1xxxx	Key A 20M to USB 3.0 A9F with EAR
5G24A20-1xxxx	Key A 20M to 3.1C 24F
5G24A25-1xxxx	Key A 20M to C24M
5G24A43-1xxxx	Key A 20F to USB 3.0 Int. 20F